

## SUPER Jr STUMP CUTTERS



Shown: RG1635 Trac Jr



Swing-Out Control Station



Rubber Track Undercarriage

When you need a compact stump cutter with the go-anywhere traction and floatation only tracks can provide, the Trac Jr is your solution. This Rayco-exclusive design raises the bar for compact stump cutters by offering a small machine that is truly full-featured. Rubber tracks provide excellent traction and ground pressure of less than 4 psi. Huge, 47-inch cutting width tackles big stumps and a hydraulic backfill blade makes easy work of clean-up. Only Rayco gives you a swing-out control station to provide excellent visibility in the cutting position and making for easy travel through gates in the travel position.



Shown: RG45 Super Jr

Turbo diesel power, 4 wheel drive, and a hydraulic backfill blade. And it comes in a self-propelled package that fits through a 36-inch gate. The RG45 puts together all the features customers want and fits them into a compact diesel stump cutter. Operators appreciate the large cutting dimensions as well as visibility and protection of the swing-out control station. For travel through gates, the control station swings in line. Wide floatation tires and 4-wheel drive allow the RG45 to maintain traction in challenging conditions. A hydraulic backfill blade saves time during clean up, letting you get on to the next job. Also available with wireless remote controls.



Available with Radio Remote Controls



Dual Rear Wheels for Increased Stability and Traction



Kubota 44 hp Diesel Engine

**RAYCOMFG.COM**

7

GreenStar Equipment is a division of



sales@greenstarequip.com.au

Phone 1300 767 589

Fax +61 7 3807 9327

Unit 20a/38 Eastern Service Rd,  
Stapylton QLD 4207 Australia

www.greenstarequip.com.au



**Shown: RG35 Super Jr**

The RG27 (27 hp) and RG35 (35 hp) Super Jr stump cutters bring revolutionary design changes to the ever popular Super Jr series of compact, self-propelled stump cutters. These machines are designed to give operators everything they want in a compact stump cutter and more. Compared to the competition, the Super Jr gives you wider cutting dimensions, lower center of gravity, more traction, lower ground pressure, better visibility while cutting, and easier travel through gates. Plus, the slewing ring pivot design eliminates maintenance associated with pin-style pivots and allows the machine to maintain maximum cutting depth across the entire width of the cut. The Super Jr is powered by Vanguard gasoline engines in 27 or 35 hp. Optional dual wheels provide a wider stance.



Swing Out Control Station



Hydraulic Backfill Blade (Option on RG27)



Available with Custom Trailer



Available with 27 hp or 35 hp Vanguard Engines



51-inch Cutting Width



Wide Tires Increase Traction and Floatation

**800.392.2686**

GreenStar Equipment is a division of



# SUPER Jr STUMP CUTTERS



## SPECIFICATIONS

GENERAL	RG27		RG55		RG1635 TRAC Jr		RG45	
	US	Metric	US	Metric	US	Metric	US	Metric
Weight	1,770 lb	803 kg	1,830 lbs	831 kg	1650 lb	748 kg	2920 lb	1,143 kg
Length (Maximum)	11'4"	290 cm	11'4"	290 cm	99"	251 cm	121 1/2"	308.6 cm
Height	52"	132 cm	52"	132 cm	57"	145 cm	72.625"	184.5 cm
Width	35"	89 cm	35"	89 cm	35"	89 cm	35 1/2"	90.2 cm
Width with Dual Wheels (Maximum)	52.5"	133 cm	52.5"	133 cm	N/A	N/A	53"	134.62 cm
Ground Clearance								
Ground Drive	Single speed	Single speed	2-speed	2-speed	2-speed	2-speed	4-wheel drive, 2-speed	4-wheel drive, 2-speed
Tires	18 x 8.5-10 R4.4 ply	18 x 8.5-10 R4.4 ply	18 x 8.5-10 R4.4 ply	18 x 8.5-10 R4.4 ply	N/A	N/A	18 x 8.5-10 R4.4 ply	18 x 8.5-10 R4.4 ply
Backkill Blade	Optional	Optional	Standard	Standard	Standard	Standard	Standard	Standard
<b>ENGINE</b>								
Model	27 hp Vanguard	20 kW Vanguard	35 hp Vanguard	26 kW Vanguard	35 hp Vanguard	26 kW Vanguard	Kubota V150C-FESB, Tier 4i	Kubota V150C-FESB, Tier 4i
Gross HP	27 hp @ 3600 RPM	20 kW @ 3600 RPM	35 hp @ 3600 RPM	26 kW @ 3600 RPM	35 hp @ 3600 RPM	26 kW @ 3600 RPM	44 hp @ 3000 RPM	32.81 kw @ 3000 RPM
Maximum Rated Torque	39.5 ft lbs @ 2500 RPM	53.6 N-m	39.5 ft lbs @ 2500 RPM	53.6 n-m	52.2 ft-lb @ 2200 RPM	70.8 N-m	87 ft-lb @ 2000 RPM	117.96 N-m
Fuel Tank Capacity	6.5 gal	24.6 L	6.5 gal	24.6 L	10 gal	37.9 L	6.5 gal	24.6 L
Electrical System	12 volts/15 AMP alternator	12 volts/15 AMP alternator	12 volts/15 AMP alternator	12 volts/15 AMP alternator	12 volts/15 AMP alternator	2 volts/15 AMP alternator	12 volts/40 AMP alternator	12 volts/40 AMP alternator
<b>HYDRAULIC SYSTEM</b>								
Oil Tank Capacity	2 gal	7.6 L	2 gal	7.6 L	2 gal	7.6 L	2 gal	7.6 L
<b>CUTTING WHEEL</b>								
Wheel Diameter	17.25"	43.8 cm	17.25"	43.8 cm	17.25"	43.8 cm	20"	51 cm
Wheel Thickness	1"	3 cm	1"	3 cm	1"	2.5 cm	1-1/2"	3.8 cm
Cutting Wheel Bearings	1.5" pillow block	3.81 cm pillow block	1.5" pillow block	3.81 cm pillow block	1.5" pillow block	3.8 cm pillow block	1 3/4" pillow block	4.45 cm pillow block
Cutting Teeth	Rayco Super tooth™	Rayco Super tooth™	Rayco Super tooth™	Rayco Super tooth™	Rayco Super tooth™	Rayco Super Tooth™	Rayco Super Tooth™	Rayco Super Tooth™
Cutter Teeth Quantity	18	18	18	18	18	18	24	24
Cutter Wheel Engagement	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system	Electromagnetic clutch with the "Quick Stop" brake system
<b>CUTTING RANGE WITHOUT REPOSITIONING</b>								
Below Ground Level	12"	30 cm	12"	30 cm	12"	30 cm	14"	14"
Above Ground Level	24.5"	62.2 cm	24.5"	62.2 cm	20"	51 cm	23.5"	23.5"
Cutting Width	51"	130 cm	51"	130 cm	47.5"	120.7 cm	60"	60"